

Cell SFP

Small Form-Factor Pluggable Transceiver 10G (BWDM) BX XFP

Product Overview

10G XFP BX Features

- Compliant with XFP MSA INF-8077i
- Compliant with IEEE802.3ae 10GBASE-BX and Ethernet Standard
- Wavelength : 1330/1270nm
- Differential LVPECL inputs and CML outputs
- Bi-Direction link distance up to 10 km, 20 km and 40km
- Connector type : Simplex LC connector
- TTL signal detect indicator
- Hot Pluggable
- Class 1 laser product complies with EN 60825-1
- RoHS Compliant



10G XFP BX

10Gbps BWDM (BX) XFP

Model No.	Data Rate	Wavelength/ Light Source	Media Type	Reach	TX Power (dBm)	RX Sens. (dBm)	Temp. (°C)	Notes
XFP-10GBX-10-33	10G	Tx1330/Rx1270	LC	10km	-5~0	<-14	0 ~ 70	BWDM (10GbE)
XFP-10GBX-10-27	10G	Rx1330/Tx1270	LC	10km	-5~0	<-14	0 ~ 70	BWDM (10GbE)
XFP-10GBX-20-33	10G	Tx1330/Rx1270	LC	20km	-2~3	<-14	0 ~ 70	BWDM (10GbE)
XFP-10GBX-20-27	10G	Rx1330/Tx1270	LC	20km	-2~3	<-14	0 ~ 70	BWDM (10GbE)
XFP-10GBX-40-33	10G	Tx1330/Rx1270	LC	40km	1~5	<-15	0 ~ 70	BWDM (10GbE)
XFP-10GBX-40-27	10G	Rx1330/Tx1270	LC	40km	1~5	<-15	0 ~ 70	BWDM (10GbE)

About Cell Technology

Cell Technology headquartered at Hong Kong SAR, a network & security technology provider specializes in design, develop and deliver innovative and intelligent IP packet processing platform into software and hardware appliances. Cell product solutions including Cell IPS, UTM, CMC, Janus, TMS, NetsVision and NetsAccess address the business needs that optimize the IP network performance, secure the network security and resiliency, and manage the quality of IP services. For more information, please visit www.cell-technology.net.